

**Worksaver**

**Implements  
Designed for  
Your  
Lifestyle**



# **WORKSAVER<sup>®</sup>**

## **SmoothCut Stump Grinders**

**Economical and Efficient PTO and Hydraulic powered stump grinders make stump removal fast and easy. Operator easily controls the grinder from the comfort of the tractor or skid steer seat.**



# Worksaver SmoothCut Stump Grinders

## SmoothCut Specifications

<u>Model</u>	<u>SG-26</u>	<u>SG-36</u>	<u>SG-26H</u>
Hitch	Cat. I	Cat. I/II	Univ. Skid Steer
Overall length (est.)	75-inches	80-inches	72-inches
Drive system protection	Slip clutch	Slip clutch	System pressure
Gearbox rating / ratio	60 hp / 1:1.5	100 hp / 1:1.46	60 hp / 1:1.5
Cutting wheel construction	-----welded 2 piece laminated steel-----		
Cutting wheel thickness	----- $\frac{3}{4}$ - inch-----		
Cutting wheel diameter	26-inches	36-inches	26-inches
Cutting wheel speed	810 rpm	788 rpm	810 rpm
@ 540 PTO rpm	5,515 ft./min.	7,430 ft./min.	5,515 ft./min.
Number of teeth	33	42	33
Cutting teeth construction	-----Carbide steel bolt in-----		
Cut height above ground	-----18-inches-----		
Cut depth below ground	10-inches	15-inches	10-inches
Max. cut depth per pass	5-inches	8-inches	5-inches
Max. horizontal cut	28-inches	33-inches	28-inches
Swing arc	-----45-degrees-----		
Min. power / flow required	22-PTO hp	45-PTO hp	15 gpm
Max. power / flow	50-PTO hp	100-PTO hp	25 gpm
Drive system	PTO / Series 5	PTO / Series 6	Hydraulic
PTO Speed	540 rpm	540 rpm	540 rpm @ 19.4 gpm
Weight (est.)	660 lbs.	880 lbs.	757 lbs.
Product number	811500	811550	811640

- Cutting wheel design provides a smoother cutting action and higher productivity.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- SureFoot stabilizer bar provides solid footing during operation.
- Maneuverable – goes anywhere a tractor or skid steer can; gets into tight places.
- Easy to operate – hydraulic controls allow easy operation from the seat of the power unit using existing hydraulic controls.
- Hardened bushings and grease zerks used at major pivot points for increased reliability and extended service life.
- Standard pressure relief valve for precise control of cutting feed rate.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.
- Hydraulic model has quick attach universal skid steer hitch system.

- Tractor models require two pair of remote hydraulic outlets.
- Skid steer unit has hydraulic solenoid valve requiring only one pair of remote hydraulic outlets.



**READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**



**STUMP GRINDER WILL PUT A HEAVY LOAD ON THE REAR OF YOUR TRACTOR OR SKID STEER. BE SURE THE TRACTOR OR SKID STEER IS PROPERLY EQUIPPED WITH COUNTER BALANCE WEIGHT IF REQUIRED.**



**NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR, SKID STEER, OR STUMP GRINDER WHEN YOU ARE USING EQUIPMENT**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
Phone: 217-324-5973 • Fax: 217-324-3356  
E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
Web: [www.worksaver.com](http://www.worksaver.com)

**Information Provided By:**

