

Worksaver

*Implements
Designed for
Your
Lifestyle*



WORKSAVER[®]

SmoothCut Stump Grinders

Economical and Efficient PTO and Hydraulic powered stump grinders make stump removal fast and easy. Operator easily controls the grinder from the comfort of the tractor or skid steer seat.



Worksaver SmoothCut Stump Grinders

SmoothCut Specifications

<u>Model</u>	<u>SG-26</u>	<u>SG-36</u>	<u>SG-26H</u>
Hitch	Cat. I	Cat. I/II	Univ. Skid Steer
Overall length (est.)	75-inches	80-inches	72-inches
Drive system protection	Slip clutch	Slip clutch	System pressure
Gearbox rating / ratio	60 hp / 1:1.5	100 hp / 1:1.46	60 hp / 1:1.5
Cutting wheel construction	-----welded 2 piece laminated steel-----		
Cutting wheel thickness	----- $\frac{3}{4}$ - inch-----		
Cutting wheel diameter	26-inches	36-inches	26-inches
Cutting wheel speed	810 rpm	788 rpm	810 rpm
@ 540 PTO rpm	5,515 ft./min.	7,430 ft./min.	5,515 ft./min.
Number of teeth	33	42	33
Cutting teeth construction	-----Carbide steel bolt in-----		
Cut height above ground	-----18-inches-----		
Cut depth below ground	10-inches	15-inches	10-inches
Max. cut depth per pass	5-inches	8-inches	5-inches
Max. horizontal cut	28-inches	33-inches	28-inches
Swing arc	-----45-degrees-----		
Min. power / flow required	22-PTO hp	45-PTO hp	15 gpm
Max. power / flow	50-PTO hp	100-PTO hp	25 gpm
Drive system	PTO / Series 5	PTO / Series 6	Hydraulic
PTO Speed	540 rpm	540 rpm	540 rpm @ 19.4 gpm
Weight (est.)	660 lbs.	880 lbs.	757 lbs.
Product number	811500	811550	811640

- Cutting wheel design provides a smoother cutting action and higher productivity.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- SureFoot stabilizer bar provides solid footing during operation.
- Maneuverable – goes anywhere a tractor or skid steer can; gets into tight places.
- Easy to operate – hydraulic controls allow easy operation from the seat of the power unit using existing hydraulic controls.
- Hardened bushings and grease zerks used at major pivot points for increased reliability and extended service life.
- Standard pressure relief valve for precise control of cutting feed rate.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.
- Hydraulic model has quick attach universal skid steer hitch system.

- Tractor models require two pair of remote hydraulic outlets.
- Skid steer unit has hydraulic solenoid valve requiring only one pair of remote hydraulic outlets.



READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.



STUMP GRINDER WILL PUT A HEAVY LOAD ON THE REAR OF YOUR TRACTOR OR SKID STEER. BE SURE THE TRACTOR OR SKID STEER IS PROPERLY EQUIPPED WITH COUNTER BALANCE WEIGHT IF REQUIRED.



NEVER ALLOW CHILDREN OR BYSTANDERS AROUND TRACTOR, SKID STEER, OR STUMP GRINDER WHEN YOU ARE USING EQUIPMENT

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100
Phone: 217-324-5973 • Fax: 217-324-3356
E-mail: sales@worksaver.com
Web: www.worksaver.com

Information Provided By:

