



Designed. Engineered. Remarkable Value.

20-Series Snow Pushers Designed for Sub-Compact Tractors



Worksaver's 20-Series Snow Pusher makes snow removal easy.

Performance matched to fit Sub-Compact tractors up to 30 HP, the 20-Series snow pushers are sized to the tractor for maximum snow removal. Available in widths of 4' or 5', these pushers are offered with either a ultra rubber cutting edge or alloy steel cutting edge.

CNC formed 11-gauge mold-board with formed 10-gauge back brace for strength and durability make these snow pushers high performers.

Models are available with "universal" skid steer style mount or John Deere hook and pin style quick attach.



worksaver.com

Engineered, Designed and Manufactured in the USA

20-Series Snow Pusher Specifications

20-Series for Sub-Compact tractors up to 30 HP, Max. operating weight 1,800 lbs.
"Universal" Skid Steer Attach



End plates with gentle slope design



Adjustable Skid Shoes of AR-400 material

| | SPS-2048R | SPS-2048M | SPS-2060R | SPS-2060M |
|--------------------------|---------------|-----------------|---------------|-----------------|
| Overall Width (in/mm) | 52 / 1321 | 52 / 1321 | 64 / 1626 | 64 / 1626 |
| Overall Height (in/mm) | 21.5 / 546 | 21.5 / 546 | 21.5 / 546 | 21.5 / 546 |
| Overall Depth (in/mm) | 21 / 533 | 21 / 533 | 21 / 533 | 21 / 533 |
| Moldboard Thickness | 11-gauge | 11-gauge | 11-gauge | 11-gauge |
| End Plate Thickness | 7-gauge | 7-gauge | 7-gauge | 7-gauge |
| Inside Angle Bracing | Yes | Yes | Yes | Yes |
| Rubber Cutting Edge | Yes (1" x 4") | No | Yes (1" x 4") | No |
| Alloy Steel Cutting Edge | No | Yes (3/8" x 4") | No | Yes (3/8" x 4") |
| Skid Shoes of AR-400 | Yes | Yes | Yes | Yes |
| Horsepower rating | Up to 30 HP | Up to 30 HP | Up to 30 HP | Up to 30 HP |
| Weight (lbs./kg) | 146 / 66 | 163 / 74 | 159 / 72 | 180 / 82 |
| Product No. | 358160 | 358165 | 358170 | 358175 |
| Optional Pull-back Kit | 358200 | 358200 | 358205 | 358205 |

20-Series for Sub-Compact tractors up to 30 HP, Max. operating weight 1,800 lbs.
John Deere hook & pin quick attach for 200/300, D120, H120, H130

| | SPJD-2048R | SPJD-2048M | SPJD-2060R | SPJD-2060M |
|--------------------------|---------------|-----------------|---------------|-----------------|
| Overall Width (in/mm) | 52 / 1321 | 52 / 1321 | 64 / 1626 | 64 / 1626 |
| Overall Height (in/mm) | 21.5 / 546 | 21.5 / 546 | 21.5 / 546 | 21.5 / 546 |
| Overall Depth (in/mm) | 21 / 533 | 21 / 533 | 21 / 533 | 21 / 533 |
| Moldboard Thickness | 11-gauge | 11-gauge | 11-gauge | 11-gauge |
| End Plate Thickness | 7-gauge | 7-gauge | 7-gauge | 7-gauge |
| Inside Angle Bracing | Yes | Yes | Yes | Yes |
| Rubber Cutting Edge | Yes (1" x 4") | No | Yes (1" x 4") | No |
| Alloy Steel Cutting Edge | No | Yes (3/8" x 4") | No | Yes (3/8" x 4") |
| Skid Shoes of AR-400 | Yes | Yes | Yes | Yes |
| Horsepower rating | Up to 30 HP | Up to 30 HP | Up to 30 HP | Up to 30 HP |
| Weight (lbs./kg) | 131 / 59 | 148 / 67 | 145 / 66 | 166 / 75 |
| Product No. | 358180 | 358185 | 358190 | 358195 |
| Optional Pull-back Kit | 358200 | 358200 | 358205 | 358205 |



Caution — A heavy load can cause your power unit to tip over. When moving heavy loads, keep the load as close to the ground as possible, go slowly around turns, and be sure the front or rear of power unit is properly counterbalanced with weights.

Caution — Operators must read & understand operator's manual, particularly the safety warnings and instructions. **The operator is responsible for safety of themselves and others when operating equipment.**



WORKSAVER, INC. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. WORKSAVER, INC. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.



Distributed by:



Worksaver, Inc.

P.O. Box 100, Litchfield, IL 62056-0100

Phone: 217-324-5973 • Fax: 217-324-3356

worksaver.com • E-mail: sales@worksaver.com

Designed. Engineered. Remarkable Value.

